

WELLHEAD NATURAL GAS



Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Version: 1.1 Revision Date: 05/21/2015

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY

Product Identifier

Product Form: Mixture

Product Name: Wellhead Natural Gas

Synonyms: Wellhead Gas, Raw Gas, Methane, Residue Gas, Natural Gas Sweet, Marsh Gas, Fuel Gas, Petroleum Gas.

CAS No. 74-82-8

Intended Use of the Product

Use of the Substance/Mixture: Industrial use

Name, Address, and Telephone of the Responsible Party

Company

Williams, Inc.
One Williams Center
Tulsa, OK 74172, US
T 800-945-5426
ehs@williams.com

Emergency Telephone Number

Emergency number Chemtrec - 800-424-9300

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Simple Asphy


Flam. Gas 1 H220

Compressed gas H280

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US) :



Signal Word (GHS-US) : Danger

WELLHEAD NATURAL GAS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- Hazard Statements (GHS-US)** : H220 - Extremely flammable gas
H280 - Contains gas under pressure; may explode if heated
May displace oxygen and cause rapid suffocation
- Precautionary Statements (GHS-US)** : P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking.
P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely
P381 - Eliminate all ignition sources if safe to do so
P403 - Store in a well-ventilated place
P410+P403 - Protect from sunlight. Store in a well-ventilated place

Other Hazards

Other Hazards Not Contributing to the Classification: Contains hydrogen sulfide. Hydrogen sulfide is a highly flammable, explosive gas under certain conditions, is a toxic gas, and may be fatal. Gas can accumulate in the headspace of closed containers, use caution when opening sealed containers. Heating the product or containers can cause thermal decomposition of the product and release hydrogen sulfide. Exposure may aggravate those with pre existing eye, skin, or respiratory conditions.

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

NAME	PRODUCT IDENTIFIER	% (W/W)	CLASSIFICATION (GHS-US)
Methane	(CAS No) 74-82-8	> 75	Simple Asphy Flam. Gas 1, H220 Liquefied gas, H280
Ethane	(CAS No) 74-84-0	< 20	Simple Asphy Flam. Gas 1, H220 Liquefied gas, H280
Propane	(CAS No) 74-98-6	< 10	Simple Asphy Flam. Gas 1, H220 Liquefied gas, H280
Carbon dioxide	(CAS No) 124-38-9	< 10	Simple Asphy Compressed gas, H280
Butane	(CAS No) 106-97-8	< 5	Simple Asphy Flam. Gas 1, H220 Liquefied gas, H280
Nitrogen	(CAS No) 7727-37-9	< 5	Simple Asphy Compressed gas, H280
Hydrogen sulfide	(CAS No) 7783-06-4	<= 0.0004	Flam. Gas 1, H220 Liquefied gas, H280 Acute Tox. 2 (Inhalation:gas), H330 Aquatic Acute 1, H400

Full text of H-phrases: see section 16

WELLHEAD NATURAL GAS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). If frostbite or freezing occurs, immediately flush with plenty of lukewarm water to GENTLY warm the affected area. Do not use hot water. Do not rub affected area. Get immediate medical attention.

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation persists. Thaw frosted parts with lukewarm water. Do not rub affected area.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation persists

Ingestion: Rinse mouth. Do NOT induce vomiting. Get immediate medical attention.

Most Important Symptoms and Effects Both Acute and Delayed

General: May cause frostbite on contact with the liquid. Butane is an asphyxiant. Lack of oxygen can be fatal

Inhalation: Gas can be toxic as a simple asphyxiant by displacing oxygen from the air. Asphyxia by lack of oxygen: risk of death. May cause drowsiness or dizziness

Skin Contact: Contact with the liquid may cause cold burns/frostbite

Eye Contact: This gas is non-irritating; but direct contact with liquefied/pressurized gas or frost particles may produce severe and possibly permanent eye damage from freeze burns

Ingestion: Ingestion is not considered a potential route of exposure. Non-irritating; but solid and liquid forms of this material and pressurized gas may cause freeze burns.

Chronic Symptoms: Contains a small amount of Hydrogen Sulfide, symptoms of overexposure are headaches, dizziness, nausea, coughing, respiratory irritation, eye irritation, skin irritation, pain in the nose, and loss of consciousness. Heating of the product may release higher amounts of Hydrogen Sulfide (H₂S).

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

SECTION 5: FIREFIGHTING MEASURES

NFPA 704 Hazard Class

Health: 1 Flammability: 4 Instability: 0



0 (Minimal)
1 (Slight)
2 (Moderate)
3 (Serious)
4 (Severe)

WELLHEAD NATURAL GAS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Extinguishing Media

Suitable Extinguishing Media: Foam, dry chemical, carbon dioxide, water spray, fog.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Extremely flammable gas

Explosion Hazard: May form flammable/explosive vapor-air mixture. Heating may cause an explosion. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

Reactivity: Hazardous reactions will not occur under normal conditions.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire

Firefighting Instructions: Leaking gas fire: Do not extinguish, unless leak can be stopped safely. In case of leaking gas fire, eliminate all ignition sources if safe to do so. Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Hydrocarbon, sulfur dioxide (SO₂), and Hydrogen sulfide (H₂S) fatal and irritating gases.

Other information: Do not allow run-off from fire fighting to enter drains or water courses

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Use special care to avoid static electric charges. Eliminate every possible source of ignition. Keep away from heat/sparks/open flames/hot surfaces - No smoking. Avoid breathing (gas, vapor, mist, spray). Use only outdoors or in a well-ventilated area. Ruptured cylinders may rocket. Do not allow product to spread into the environment.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

WELLHEAD NATURAL GAS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methods and Material for Containment and Cleaning Up

For Containment: Notify authorities if liquid enters sewers or public waters. Use only non-sparking tools.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. Isolate area until gas has dispersed. Use water spray to disperse vapors. For water based spills contact appropriate authorities and abide by local regulations for hydrocarbon spills into waterways. Contact competent authorities after a spill.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: Handle empty containers with care because residual vapors are flammable. Extremely flammable gas. Do not pressurize, cut, or weld containers. Do not puncture or incinerate container. Liquid gas can cause frost-type burns. If stored under heat for extended periods or significantly agitated, this material might evolve or release hydrogen sulfide, a toxic, flammable gas, which can raise and widen this material's actual flammability limits and significantly lower its auto-ignition temperature. Hydrogen sulfide can be fatal.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do not eat, drink or smoke when using this product

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Proper grounding procedures to avoid static electricity should be followed. Comply with applicable regulations.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep in fireproof place. Store in a well-ventilated place. Keep container tightly closed. Keep/Store away from extremely high or low temperatures, ignition sources, direct sunlight, incompatible materials. Store in original container.

Incompatible Materials: Strong acids, strong bases, strong oxidizers, chlorine, halogenated compounds.

Specific End Use(s) Industrial use

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Chemical Name	ACGIH	OSHA	NIOSH
Methane	STEL: 1000 ppm	--	REL (TWA): 800 ppm REL (TWA):1900 mg/m ³
Ethane	Minimal oxygen content - asphyxia	1926.55 - Simple asphyxiant	--
Propane	Minimal oxygen content - asphyxia	TWA: 1000 ppm TWA: 1800 mg/m ³	REL (TWA): 1000 ppm REL (TWA):1800 mg/m ³ IDLH: 2100 PPM (10%)

WELLHEAD NATURAL GAS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carbon dioxide	TWA: 5000 ppm STEL: 30000 ppm	PEL (TWA): 5000 ppm PEL (TWA): 9000 mg/m ³	REL (TWA): 5000 ppm REL (TWA): 9000 mg/m ³ REL (STEL): 30000 ppm REL (STEL): 54000 mg/m ³ IDLH: 40000 mg/m ³
Butane	STEL: 1000 ppm	--	REL (TWA): 800 ppm REL (TWA): 1900 mg/m ³
Hydrogen Sulfide	STEL: 5 ppm TWA: 1 ppm	1910.1000 - Ceiling: 20 ppm 1926.55 - TWA: 15 mg/m ³ 1926.55 - TWA: 10 ppm	REL (Ceiling): 10 ppm REL (Ceiling): 15 mg/m ³ IDLH: 100 ppm

Note: State province, local or other agencies or advisory groups may have established more stringent limits. Consult an industrial hygienist or similar professional, or your local agencies, for further information.

Exposure Controls

Appropriate Engineering Controls: Gas detectors should be used when flammable gases/vapours may be released. Ensure adequate ventilation, especially in confined areas. Proper grounding procedures to avoid static electricity should be followed. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use explosion-proof equipment

Personal Protective Equipment: Protective goggles. Protective clothing. Respiratory protection of the dependent type. Insulated gloves.



Materials for Protective Clothing: Chemically resistant materials and fabrics. Wear fire/flammable resistant/retardant clothing.

Hand Protection: Wear chemically resistant protective gloves. Insulated gloves

Eye Protection: Chemical goggles or safety glasses.

Skin and Body Protection: Wear appropriate protective clothing.

Respiratory Protection: Use a NIOSH-approved self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

Thermal Hazard Protection: Wear suitable protective clothing.

Other Information: When using, do not eat, drink or smoke.

WELLHEAD NATURAL GAS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Gas
Appearance	: Clear, Colorless gas
Odor	: Gasoline-like or natural gas odor. May contain hydrogen sulfide, which has a rotten egg odor.
Odor Threshold	: Not available
pH	: Not available
Relative Evaporation Rate (butylacetate=1)	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: -157 °C (-250.6°F)
Flash Point	: -187 °C (-304.6°F)
Auto-ignition Temperature	: > 288 °C (>550.4°F)
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Extremely flammable gas
Lower Flammable Limit	: 3 %
Upper Flammable Limit	: 17 %
Vapor Pressure	: 40 mm Hg @25°C (77°F)
Relative Vapor Density at 20 °C	: 0.6 (air = 1)
Relative Density	: Not available
Specific Gravity	: Not available
Solubility	: Negligible
Log Pow	: Not available
Log Kow	: Not available
Viscosity, Kinematic	: Not available
Viscosity, Dynamic	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not available
Explosion Data – Sensitivity to Static Discharge	: Static Discharge could act as an ignition source

WELLHEAD NATURAL GAS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Hazardous reactions will not occur under normal conditions.

Chemical Stability: Extremely flammable gas. Stable at standard temperature and pressure.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks. Incompatible materials. Avoid ignition sources.

Incompatible Materials: Strong acids, strong bases, strong oxidizers, halogenated compounds, chlorine.

Hazardous Decomposition Products: Carbon oxides (CO, CO₂). Hydrocarbons. Sulfur dioxide and hydrogen sulfide are fatal and irritating gases.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Not classified

Serious Eye Damage/Irritation: Not classified

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not available

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries after Inhalation: Gas can be toxic as a simple asphyxiant by displacing oxygen from the air. Asphyxia by lack of oxygen: risk of death. May cause drowsiness or dizziness.

Symptoms/Injuries after Skin Contact: Contact with the liquid may cause cold burns/frostbite.

Symptoms/Injuries after Eye Contact: This gas is non-irritating; but direct contact with liquefied/pressurized gas or frost particles may produce severe and possibly permanent eye damage from freeze burns.

Symptoms/Injuries after Ingestion: Ingestion is not considered a potential route of exposure. Non-irritating; but solid and liquid forms of this material and pressurized gas may cause freeze burns.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data

ETHANE (74-84-0)	
LC50 Inhalation Rat (mg/l)	658 mg/l (Exposure time: 4 h)

WELLHEAD NATURAL GAS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

PROPANE (74-98-6)	
LC50 Inhalation Rat (mg/l)	658 mg/l (Exposure time: 4 h)
BUTANE (106-97-8)	
LC50 Inhalation Rat (mg/l)	LC50 Inhalation Rat (mg/l)
HYDROGEN SULFIDE (7783-06-4)	
LC50 Inhalation Rat (mg/l)	0.99 mg/l (Exposure time: 1 h)
ATE (gases)	100.000 ppmV/4h

SECTION 12: ECOLOGICAL INFORMATION

GHS Classification:

No classified hazards

Toxicity:

WELLHEAD NATURAL GAS (CAS MIXTURE)	
LC50 Fish 1	0.002 mg/l (Exposure time: 96 h - Species: Coregonus clupeaformis)
HYDROGEN SULFIDE (7783-06-4)	
LC50 Fish 1	0.0448 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through])
EC50 Daphnia 1	0.022 mg/l (Exposure time: 96 h - Species: Gammarus pseudolimnaeus)
LC 50 Fish 2	0.016 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

Persistence and Degradability

WELLHEAD NATURAL GAS	
Persistence and Degradability	Product is biodegradable.

Bioaccumulative Potential

WELLHEAD NATURAL GAS	
Bioaccumulative Potential	Not expected to bioaccumulate.
ETHANE (74-84-0)	
Log Pow	<= 2.8
PROPANE (74-98-6)	
Log Pow	2.3

WELLHEAD NATURAL GAS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

BUTANE (106-97-8)	
Log Pow	2.89
CARBON DIOXIDE (124-38-9)	
BCF fish 1	(no bioaccumulation)
Log Pow	0.83
HYDROGEN SULFIDE (7783-06-4)	
BCF fish 1	(no bioaccumulation)
Log Pow	0.45 (at 25 °C)

Mobility in Soil Not available

Other Adverse Effects

Other adverse effects: Can cause frost damage to vegetation. Has photochemical ozone creation potential.

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Additional Information: Handle empty containers with care because residual vapors are flammable. Empty gas cylinders should be returned to the vendor for recycling or refilling.

SECTION 14: TRANSPORT INFORMATION

UN Number

UN-No.(DOT): 1971

DOT NA no.: UN1971

UN Proper Shipping Name

DOT Proper Shipping Name : UN1971, Natural gas, compressed (with high methane content), 2.1

Hazard Labels (DOT) : 2.1 - Flammable gases



DOT Packaging Exceptions (49 CFR 173.xxx) : 306

DOT Packaging Non Bulk (49 CFR 173.xxx) : 302

DOT Packaging Bulk (49 CFR 173.xxx) : 302

Additional Information

Emergency Response Guide (ERG) Number : 115

WELLHEAD NATURAL GAS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Transport by sea

DOT Vessel Stowage Location : E - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length, but is prohibited from carriage on passenger vessels in which the limiting number of passengers is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Air transport

DOT Quantity Limitations Passenger Aircraft/Rail (49 CFR 173.27) : Forbidden

DOT Quantity Limitations Cargo Aircraft Only (49 CFR 175.75) : 150 kg

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Wellhead Natural Gas	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Sudden release of pressure hazard



Listed on the United States TSCA (Toxic Substances Control Act) inventory

Methane (74-82-8)
Ethane (74-84-0)
Propane (74-98-6)
Butane (106-97-8)
Carbon dioxide (124-38-9)
Nitrogen (7727-37-9)

Hydrogen sulfide (7783-06-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on SARA Section 302 (Specific toxic chemical listings)	
Listed on SARA Section 313 (Specific toxic chemical listings)	
SARA Section 302 Threshold Planning Quantity (TPQ)	500
SARA Section 313 - Emission Reporting	1.0 %

Canadian Regulations

WELLHEAD NATURAL GAS	
WHMIS Classification	Class B Division 1 - Flammable Gas Class A - Compressed Gas
	

WELLHEAD NATURAL GAS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Propane (74-98-6)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas
Butane (106-97-8)	
Listed on the Canadian DSL (Domestic Substances List) inventory. Listed on the Canadian Ingredient Disclosure List	
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas
Carbon dioxide (124-38-9)	
Listed on the Canadian DSL (Domestic Substances List) inventory. Listed on the Canadian Ingredient Disclosure List	
WHMIS Classification	Class A - Compressed Gas
Nitrogen (7727-37-9)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Class A - Compressed Gas
Methane (74-82-8)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas
Ethane (74-84-0)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION

Revision date : 05/21/2015

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200

GHS Full Text Phrases:

Acute Tox. 2 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 2
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Compressed gas	Gases under pressure Compressed gas
Flam. Gas 1	Flammable gases Category 1
Liquefied gas	Gases under pressure Liquefied gas
Simple Asphy	Simple Asphyxiant
H220	Extremely flammable gas
H280	Contains gas under pressure; may explode if heated
H330	Fatal if inhaled
H400	Very toxic to aquatic life

WELLHEAD NATURAL GAS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Guide to Abbreviations:

ACGIH = American Conference of Governmental Industrial Hygienists; CASRN = Chemical Abstracts Service Registry Number; CEILING = Ceiling Limit (15 minutes); CERCLA = The Comprehensive Environmental Response, Compensation, and Liability Act; EPA = Environmental Protection Agency; GHS = Globally Harmonized System; IARC = International Agency for Research on Cancer; INSHT = National Institute for Health and Safety at Work; IOPC = International Oil Pollution Compensation; LEL = Lower Explosive Limit; NE = Not Established; NFPA = National Fire Protection Association; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration; PEL = Permissible Exposure Limit (OSHA); SARA = Superfund Amendments and Reauthorization Act; STEL = Short Term Exposure Limit (15 minutes); TLV = Threshold Limit Value (ACGIH); TWA = Time Weighted Average (8 hours); UEL = Upper Explosive Limit; WHMIS = Worker Hazardous Materials Information System (Canada)

Disclaimer of Expressed and implied Warranties:

The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THE INFORMATION PROVIDED ABOVE, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. No responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above, and the product, are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use. In addition, no authorization is given nor implied to practice any patented invention without a license.

Party Responsible for the Preparation of This Document

Williams, Inc.
One Williams Center
Tulsa, OK 74172, US
800-688-7507

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

North America GHS US 2012 & WHMIS