

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 15, 2018

Revision: October 15, 2018

1 Identification

- **Product identifier**

- **Trade name:** Wellhead Natural Gas

- **Other means of identification:**

Wellhead Gas, Raw Gas, Methane, Residue Gas, Natural Gas Sweet, Marsh Gas, Fuel Gas, Petroleum Gas

- **Recommended use and restriction on use**

- **Recommended use:** Industrial uses.

- **Restrictions on use:** No relevant information available.

- **Details of the supplier of the Safety Data Sheet**

- **Manufacturer/Supplier:**

Williams, Inc.
One Williams Center
Tulsa, OK 74172
USA
855-945-5762 (Toll-Free)
ehs@williams.com

- **Emergency telephone number:**

CHEMTREC
1-800-424-9300 (US/Canada)
+01 703-527-3887 (International)

2 Hazard(s) identification

- **Classification of the substance or mixture**

Flam. Gas 1 H220 Extremely flammable gas.

Press. Gas H280 Contains gas under pressure; may explode if heated.

Simple Asphyxiant May displace oxygen and cause rapid suffocation.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms:**



GHS02 GHS04

- **Signal word:** Danger

- **Hazard statements:**

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

May displace oxygen and cause rapid suffocation.

- **Precautionary statements:**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 Eliminate all ignition sources if safe to do so.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

(Cont'd. on page 2)



Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 15, 2018

Revision: October 15, 2018

Trade name: Wellhead Natural Gas

(Cont'd. of page 1)

- **Other hazards** There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Components:**

74-82-8	Methane	Flam. Gas 1, H220 Press. Gas, H280 Simple Asphyxiant	>75%
74-84-0	Ethane	Flam. Gas 1, H220 Press. Gas, H280 Simple Asphyxiant	<20%
74-98-6	Propane	Flam. Gas 1, H220 Press. Gas, H280 Simple Asphyxiant	<10%
124-38-9	Carbon dioxide	Press. Gas, H280 Simple Asphyxiant	<10%
106-97-8	butane	Flam. Gas 1, H220 Press. Gas, H280 Simple Asphyxiant	<5%
7727-37-9	nitrogen	Press. Gas, H280 Simple Asphyxiant	<5%
7783-06-4	Hydrogen sulfide / Hydrogen sulphide	Flam. Gas 1, H220 Press. Gas, H280 Acute Tox. 2, H330	<0.0004%

- **Additional information:**

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.
 For the wording of the listed Hazard Statements, refer to section 16.

4 First-aid measures

- **Description of first aid measures**

- **After inhalation:**

Supply fresh air.

Provide oxygen treatment if affected person has difficulty breathing.

If experiencing respiratory symptoms: Call a poison center/doctor.

- **After skin contact:**

In cases of frostbite from liquefied gas or from high-pressure systems, rinse with plenty of water. Do not remove clothing.

- **After eye contact:**

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:** Unlikely route of exposure.

- **Most important symptoms and effects, both acute and delayed:**

Dizziness

Coughing

(Cont'd. on page 3)



Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 15, 2018

Revision: October 15, 2018

Trade name: Wellhead Natural Gas

(Cont'd. of page 2)

Frostbite from liquefied gas or high-pressure systems.

Disorientation

- **Danger:** May displace oxygen and cause rapid suffocation.
- **Indication of any immediate medical attention and special treatment needed:**
If necessary oxygen respiration treatment.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
Foam
Water fog / haze
Gaseous extinguishing agents
Carbon dioxide
- **For safety reasons unsuitable extinguishing agents:** Water stream.
- **Special hazards arising from the substance or mixture**
Danger of receptacles bursting because of high vapor pressure if heated.
Extremely flammable gas.
- **Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.
- **Additional information:**
Eliminate all ignition sources if safe to do so.
In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.
Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation.
Keep away from ignition sources.
Take precautionary measures against static discharge.
Use only non-sparking tools.
Protect from heat.
For large spills, use respiratory protective device against the effects of fumes/dust/aerosol.
- **Environmental precautions** No special measures required.
- **Methods and material for containment and cleaning up** Allow to evaporate.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling**

(Cont'd. on page 4)



Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 15, 2018

Revision: October 15, 2018

Trade name: Wellhead Natural Gas

(Cont'd. of page 3)

- **Precautions for safe handling:** Use enclosed means of conveyance.
- **Information about protection against explosions and fires:**
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.
 - Ground/bond container and receiving equipment.
 - Emergency cooling must be available in case of nearby fire.
 - Flammable gas-air mixtures may be formed in empty containers/receptacles.
- **Conditions for safe storage, including any incompatibilities**
- **Requirements to be met by storerooms and receptacles:**
 - Avoid storage near extreme heat, ignition sources or open flame.
- **Information about storage in one common storage facility:** Store away from oxidizing agents.
- **Further information about storage conditions:**
 - Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.
- **Specific end use(s)** No relevant information available.

8 Exposure controls/personal protection

· Control parameters

· Components with limit values that require monitoring at the workplace:

74-82-8 Methane

TLV (USA)	refer to App. F in TLVs and BEIs book; NIC-D, EX
EL (Canada)	Simple asphyxiant, EX
EV (Canada)	Long-term value: 1,000 ppm revoked as of 01/01/18
LMPE (Mexico)	Long-term value: 1000 ppm

74-84-0 Ethane

TLV (USA)	Refer to Appendix F in TLVs & BEIs book; (D, EX)
EL (Canada)	simple asphyxiant; EX
EV (Canada)	Long-term value: 1,000 ppm revoked as of 01/01/18
LMPE (Mexico)	Long-term value: 1000 ppm

74-98-6 Propane

PEL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
TLV (USA)	refer to Appendix F in TLVs&BEIs book; D, EX
EL (Canada)	Simple asphyxiant; EX
EV (Canada)	Long-term value: 1,000 ppm revoked as of 01/01/18
LMPE (Mexico)	Long-term value: 1000 ppm

124-38-9 Carbon dioxide

PEL (USA)	Long-term value: 9000 mg/m ³ , 5000 ppm
REL (USA)	Short-term value: 54,000 mg/m ³ , 30,000 ppm Long-term value: 9000 mg/m ³ , 5000 ppm

(Cont'd. on page 5)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 15, 2018

Revision: October 15, 2018

Trade name: Wellhead Natural Gas

(Cont'd. of page 4)

TLV (USA)	Short-term value: 54,000 mg/m ³ , 30,000 ppm Long-term value: 9000 mg/m ³ , 5000 ppm
EL (Canada)	Short-term value: 15000 ppm Long-term value: 5000 ppm
EV (Canada)	Short-term value: 54,000 mg/m ³ , 30,000 ppm Long-term value: 9,000 mg/m ³ , 5,000 ppm
LMPE (Mexico)	Short-term value: 30000 ppm Long-term value: 5000 ppm

106-97-8 butane

REL (USA)	Long-term value: 1900 mg/m ³ , 800 ppm
TLV (USA)	Short-term value: 2370 mg/m ³ , 1000 ppm (EX)
EL (Canada)	Short-term value: 1000 ppm EX
EV (Canada)	Long-term value: 800 ppm revoked as of 01/01/18
LMPE (Mexico)	Long-term value: 1000 ppm

7727-37-9 nitrogen

TLV (USA)	withdrawn TLV, see App. F; simple asphyxiant
EL (Canada)	Simple asphyxiant
LMPE (Mexico)	Asfixiante simple

7783-06-4 Hydrogen sulfide / Hydrogen sulphide

PEL (USA)	Ceiling limit value: 20; 50* ppm *10-min peak; once per 8-hr shift
REL (USA)	Ceiling limit value: 15* mg/m ³ , 10* ppm *10-min
TLV (USA)	Short-term value: 7 mg/m ³ , 5 ppm Long-term value: 1.4 mg/m ³ , 1 ppm
EL (Canada)	Ceiling limit value: 10 ppm
EV (Canada)	Short-term value: 15 ppm Long-term value: 10 ppm
LMPE (Mexico)	Short-term value: 5 ppm Long-term value: 1 ppm

- **Exposure controls**

- **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

- **Engineering controls:** Provide adequate ventilation.

- **Breathing equipment:**

Not required under normal conditions of use.



Self-contained respiratory protective device should be used in case of large spills or leaks.

(Cont'd. on page 6)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 15, 2018

Revision: October 15, 2018

Trade name: Wellhead Natural Gas

(Cont'd. of page 5)

- **Protection of hands:**
Wear gloves for protection against thermal and mechanical hazards according to OSHA and NIOSH rules.
- **Eye protection:**



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

- **Body protection:** Wear appropriate protective clothing.
- **Limitation and supervision of exposure into the environment**
No relevant information available.
- **Risk management measures** No relevant information available.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· Appearance:	
Form:	Gaseous
Color:	Colorless
· Odor:	Gasoline-like or natural gas odor. May contain hydrogen sulfide, which has a rotten egg odor.
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Melting point/Melting range:	Not determined.
· Boiling point/Boiling range:	-157 °C (-250.6 °F)
· Flash point:	-187 °C (-304.6 °F)
· Flammability (solid, gaseous):	Extremely flammable gas.
· Auto-ignition temperature:	>288 °C (>550.4 °F)
· Decomposition temperature:	Not determined.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits	
Lower:	3 Vol %
Upper:	17 Vol %
· Oxidizing properties:	Not determined.
· Vapor pressure at 25 °C (77 °F):	40 mmHg (0.8 psi)
· Density:	
Relative density:	Not determined.
Vapor density:	Not determined.
Relative vapor density at 20 °C (68 °F):	0.6 (air = 1)
Evaporation rate:	Not applicable.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.

(Cont'd. on page 7)



Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 15, 2018

Revision: October 15, 2018

Trade name: Wellhead Natural Gas

(Cont'd. of page 6)

- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
- **Other information** No relevant information available.

10 Stability and reactivity

- **Reactivity:** No data available for self-reactivity.
- **Chemical stability:** Stable under normal temperatures and pressures.
- **Thermal decomposition / conditions to be avoided:**
Danger of receptacles bursting because of high vapor pressure if heated.
- **Possibility of hazardous reactions**
Extremely flammable gas.
Reacts with halogenated compounds.
Develops readily flammable gases / fumes.
Reacts with oxidizing agents.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.
Hazardous gases may be released if heated above the decomposition point.
- **Conditions to avoid**
Excessive heat.
Keep ignition sources away - Do not smoke.
- **Incompatible materials**
Oxidizers
Halogenated compounds.
- **Hazardous decomposition products**
Under fire conditions only:
Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:** Based on available data, the classification criteria are not met.
- **LD/LC50 values that are relevant for classification:** None.
- **Primary irritant effect:**
- **On the skin:** Based on available data, the classification criteria are not met.
- **On the eye:** Based on available data, the classification criteria are not met.
- **Sensitization:** Based on available data, the classification criteria are not met.

IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

NTP (National Toxicology Program):

None of the ingredients are listed.

OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

(Cont'd. on page 8)



Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 15, 2018

Revision: October 15, 2018

Trade name: Wellhead Natural Gas

(Cont'd. of page 7)

- **Probable route(s) of exposure:**
Inhalation.
Eye contact.
Skin contact.
- **Acute effects (acute toxicity, irritation and corrosivity):**
May displace oxygen and cause rapid suffocation.
- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.
- **Carcinogenicity:** Based on available data, the classification criteria are not met.
- **Reproductive toxicity:** Based on available data, the classification criteria are not met.
- **STOT-single exposure:** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure:** Based on available data, the classification criteria are not met.
- **Aspiration hazard:** Based on available data, the classification criteria are not met.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity** No relevant information available.
- **Persistence and degradability** No relevant information available.
- **Bioaccumulative potential:** No relevant information available.
- **Mobility in soil:** No relevant information available.
- **Additional ecological information**
- **General notes:** Not known to be hazardous to water.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Contact waste processors for recycling information.
The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.
- **Uncleaned packagings**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1971
- **UN proper shipping name**
- **DOT, IATA** Natural gas, compressed

(Cont'd. on page 9)

Safety Data Sheet





acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 15, 2018

Revision: October 15, 2018

Trade name: Wellhead Natural Gas

(Cont'd. of page 8)

· ADR, IMDG	NATURAL GAS, COMPRESSED
· Transport hazard class(es)	
· DOT	
	
· Class	2.1
· Label	2.1
· ADR	
	
· Class	2.1 1F
· Label	2.1
· IMDG, IATA	
	
· Class	2.1
· Label	2.1
· Packing group	This UN-number is not assigned a packing group.
· Environmental hazards	
· Marine pollutant:	No
· Special precautions for user	Not applicable.
· Danger code (Kemler):	21
· EMS Number:	F-D,S-U
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· IATA	
	Cargo Aircraft Only.

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- United States (USA)

(Cont'd. on page 10)

**Safety Data Sheet**

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 15, 2018

Revision: October 15, 2018

Trade name: Wellhead Natural Gas

(Cont'd. of page 9)

· SARA**· Section 302 (extremely hazardous substances):**

None of the ingredients are listed.

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act)

All ingredients are listed.

· Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

74-82-8	Methane	10000
74-84-0	Ethane	10000
74-98-6	Propane	10000
106-97-8	butane	10000

· Proposition 65 (California)**· Chemicals known to cause cancer:**

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· EPA (Environmental Protection Agency):

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· Canadian Domestic Substances List (DSL) (Substances not listed.):

All ingredients are listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bio-accumulable, Toxic
 vPvB: very Persistent and very Bioaccumulative

(Cont'd. on page 11)



Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 15, 2018

Revision: October 15, 2018

Trade name: Wellhead Natural Gas

(Cont'd. of page 10)

OSHA: Occupational Safety & Health Administration
Flam. Gas 1: Flammable gases – Category 1
Press. Gas: Gases under pressure – Compressed gas
Press. Gas: Gases under pressure – Liquefied gas
Acute Tox. 2: Acute toxicity – Category 2

• **Sources**

Website, European Chemicals Agency (echa.europa.eu)
Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor_internet/registry/substreg/home/overview/home.do)
Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)
Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6
Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.
Safety Data Sheets, Individual Manufacturers

SDS Prepared by:
ChemTel Inc.
1305 North Florida Avenue
Tampa, Florida USA 33602-2902
Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573
Website: www.chemtelinc.com